

view
en



Display Engine

PDE-i945
GM-32/42



SAW Touch

en
en
en



PDE-i945 Series

Specificatii



	PDE-i945-1.5U	PDE-i945-1U
Sistem		
Procesor	Suport pentru procesor Intel Core Duo/Core 2 Duo	Suport pentru procesor Intel Core Duo/Core 2 Duo
Memorie	2x DDRII 533/667MHz pana la 3GB	2x DDRII 533/667MHz pana la 4GB
Chipset	Intel 945GM + ICH7M	Intel 945GM + ICH7M
Ceas timp real	Chipset cu baterie de litiu atasata	Chipset cu baterie de litiu atasata
Temporizator	Reset de sistem cu temporizator intre 1~255sec.	Reset de sistem cu temporizator intre 1~255sec.
Interfata SATA	Porturi 2x SATA 300, setari implicite SATA 80GB	Porturi 2x SATA 300, setari implicite SATA 80GB
Interfata VGA	Chipset integrat Intel GMA 950	Chipset integrat Intel GMA 950
Interfata LVDS	Conector de tip 18bits dual channel LVDS	Conector de tip 18bits dual channel LVDS
Interfata LAN	Interfata LAN Intel 82537L Gigabit, 1x port Ethernet RJ-45	2x Marvell 88E8053 GbE, 2x porturi Ethernet RJ-45
Disc Solid State	Suport pentru interfata IDE 44Pin si sursa alimentare +5V	Suport pentru interfata IDE 44Pin si sursa alimentare +5V
	1x Compact Flash	1x Compact Flash
Interfata extinsa	Suporta Slot PCI Express x1 si x16	2x sloturi PCI
	2x Mini PCI Type III	N/A
Port extern I/E	1x port serial RS232, 1x RS232/422/485	1x port serial RS232, 1x RS232/422/485
	2x porturi USB2.0, 1x port firewire IEEE 1394, 1x port parallel	4x porturi USB2.0
	1x iesire S-Video si Composite, 1x I/E placa sunet, 1x intrare microfon	1x iesire S-Video si Composite, 1x I/E placa sunet, 1x intrare microfon
Interfata monitor	Conector VGA Dsub 15pin	Conector VGA Dsub 15pin, conectori DVI
Caracteristici		
Sursa alimentare	200Watt, AC-DC PSU ATX cu PFC	200Watt, AC-DC PSU ATX cu PFC
Dimensiuni	432(lungime) x 221(latime) x 65(inaltime)mm	432(lungime) x 281(latime) x 44(inaltime)mm
Sistem de operare	Compatibil cu Windows 98/Me/Nt/2000/Xp/Xp embedded	Compatibil cu Windows 98/Me/Nt/2000/Xp/Xp embedded
Certificare	CE, FCC Class A	CE, FCC Class A
Optionale	Slim DVD, modul WiFi b+g, placa TV-tuner nVidia PCI-e x16 memorie 256MB DDR2 (profil mic)	Placa TV-tuner PCI memorie Ati PCI 128MB DDR (profil mic)

GM Series



Display

Model	GM-32 / GM-42
Tip Display	Active Matrix TFT LCD ; 32" / 42"
Dimensiuni	784W x 474H x 107D / 1030W X 635H x 112D mm
Rezolutie maxima	1366 x 768 / 1366 x 768
Culori	16.7 milioane/16.7 milioane
Luminozitate	500cd/m ² / 500cd/m ²
Raport contrast	1000 : 1 / 800 : 1
Conector semnal intrare	RGB Analog, D-Sub 15 Pin Female
Caracteristici	
Touch Panel	SAW Type (Optional)
Culoare carcasa	Negru sau negru cu argintiu pentru suport
Sursa alimentare	Interna: 200/270W
Temperatura si umiditate	In functionare: 0 C - 40 C, 10% - 90%
Instalare	Suport de montare pe suprafata plana sau pe perete



www.quartzmatrix.com

B-dul Carol I, nr. 5, Iasi

Tel.: 0232 - 217.248

Fax: 0232-217.262

E-mail: office@quartzmatrix.ro



www.countek.ro